


SELF-LOCKING HEXAGON NUT WITH NYLON INSERT

ZESKANT BORGMOER MET KUNSTSTOF RING

ECROU AUTOSERRANT HEXAGONAL AVEC ANNEAU NYLON

SECHSKANTSICHERUNGSMUTTER MIT KUNSTSTOFF RING



material : Steel class [6]	materiaal : Staal Klasse [6]	matière : Acier classe [6]	Werkstoff : Stahl Klasse [6]
type : standard	type : standaard	type : standard	Typ : normalmass
surface : zinc plated Cr3+	oppervlak : verzinkt Cr3+	surface : zingué Cr3+	Oberfläche : verzinkt Cr3+

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
3	00985,03 Z	00098580100303	5410439069892	200	6.01	4	2.4	5.5
4	00985,04 Z	00098580100403	5410439069915	200	7.66	5	2.9	7
5	00985,05 Z	00098580100503	5410439069939	200	8.79	5	3.2	8



material : Steel class [8]	materiaal : Staal Klasse [8]	matière : Acier classe [8]	Werkstoff : Stahl Klasse [8]
type : standard	type : standaard	type : standard	Typ : normalmass
surface : zinc plated Cr3+	oppervlak : verzinkt Cr3+	surface : zingué Cr3+	Oberfläche : verzinkt Cr3+

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
6	00985,06 Z	00098580100603	5410439101455	200	11.05	6	4	10
7	00985,07 Z	00098580100703	5410439069984	200	12.12	7.5	4.7	11
8	00985,08 Z	00098580100803	5410439070003	200	14.38	8	5.5	13
10	00985,10 Z	00098580101003	5410439070034	200	18.9	10	6.5	17
12	00985,12 Z	00098580101203	5410439070065	200	21.1	12	8	19
14	00985,14 Z	00098580101403	5410439070096	100	24.49	14	9.5	22
16	00985,16 Z	00098580101603	5410439070126	100	26.75	16	10	24
18	00985,18 Z	00098580101803	5410439070157	50	29.56	18.5	13	27
20	00985,20 Z	00098580102003	5410439070188	50	32.95	20	14	30
22	00985,22 Z	00098580102203	5410439070218	25	35.03	22	15	32
24	00985,24 Z	00098580102403	5410439070249	25	39.55	24	15	36
27	00985,27 Z	00098580102703	5410439070263	25	45.2	27	17	41
30	00985,30 Z	00098580103003	5410439070287	25	50.85	30	19	46



material : Steel class 10	materiaal : Staal klasse 10	matière : Acier classe 10	Werkstoff : Stahl Klasse 10
type : standard	type : standaard	type : standard	Typ : normalmass
surface : zinc plated Cr3+	oppervlak : verzinkt Cr3+	surface : zingué Cr3+	Oberfläche : verzinkt Cr3+

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
6	00985,06 Z-	00098510100603	5410439069977	200	11.05	6	4	10
8	00985,08 Z-	00098510100803	5410439070010	200	14.38	8	5.5	13
10	00985,10 Z-	00098510101003	5410439070041	200	18.9	10	6.5	17
12	00985,12 Z-	00098510101203	5410439070072	200	21.1	12	8	19
14	00985,14 Z-	00098510101403	5410439070102	100	24.49	14	9.5	22
16	00985,16 Z-	00098510101603	5410439070133	100	26.75	16	10	24
18	00985,18 Z-	00098510101803	5410439070164	50	29.56	18.5	13	27
20	00985,20 Z-	00098510102003	5410439070195	50	32.95	20	14	30
22	00985,22 Z-	00098510102203	5410439070225	25	35.03	22	15	32
24	00985,24 Z-	00098510102403	5410439070256	25	39.55	24	15	36
27	00985,27 Z-	00098510102703	5410439070270	25	45.2	27	17	41
30	00985,30 Z-	00098510103003	5410439070294	25	50.85	30	19	46
36	00985,36 Z-	00098510103603	5410439269520	10	60.79	36	25	55



material : Stainless steel A2	materiaal : Roestvast staal A2	matière : Inox A2	Werkstoff : Edelstahl A2
type : standard	type : standaard	type : standard	Typ : normalmass
surface : plain	oppervlak : blank	surface : brut	Oberfläche : roh

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
3	00985,03 A2	000985A7000303	5410439069885	200	6.01	4	2.4	5.5
4	00985,04 A2	000985A7000403	5410439069908	200	7.66	5	2.9	7
5	00985,05 A2	000985A7000503	5410439069922	200	8.79	5	3.2	8
6	00985,06 A2	000985A7000603	5410439069953	200	11.05	6	4	10
8	00985,08 A2	000985A7000803	5410439069991	200	14.38	8	5.5	13
10	00985,10 A2	000985A7001003	5410439070027	200	18.9	10	6.5	17
12	00985,12 A2	000985A7001203	5410439070058	200	21.1	12	8	19
14	00985,14 A2	000985A7001403	5410439070089	100	24.49	14	9.5	22
16	00985,16 A2	000985A7001603	5410439070119	50	26.75	16	10	24
18	00985,18 A2	000985A7001803	5410439070140	50	29.56	18.5	13	27
20	00985,20 A2	000985A7002003	5410439070171	50	32.95	20	14	30
24	00985,24 A2	000985A7002403	5410439070232	25	39.55	24	15	36



material : Steel class 6	materiaal : Staal klasse 6	matière : Acier classe 6	Werkstoff : Stahl Klasse 6
type : metric fine thread	type : metrisch fijn	type : filet métrique fin	Typ : metrisch Feingewinde
surface : zinc plated Cr3+	oppervlak : verzinkt Cr3+	surface : zingué Cr3+	Oberfläche : verzinkt Cr3+

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
8	MF985,08100 Z	OMF985001008001003	5410439130943	200	14.38	8	5.5	13
10	MF985,10100 Z	OMF985001010001003	5410439127592	200	18.9	10	6.5	17
10	MF985,10125 Z	OMF985001010001253	5410439130950	200	18.9	10	6.5	17
12	MF985,12125 Z	OMF985001012001253	5410439423793	200	21.1	12	8	19
12	MF985,12150 Z	OMF985001012001503	5410439109932	200	21.1	12	8	19
14	MF985,14150 Z	OMF985001014001503	5410439108096	100	24.49	14	9.5	22
16	MF985,16150 Z	OMF985001016001503	5410439203463	100	26.75	16	10	24
18	MF985,18150 Z	OMF985001018001503	5410439235570	50	29.56	18.5	13	27
20	MF985,20150 Z	OMF985001020001503	5410439130974	50	32.95	20	14	30
22	MF985,22150 Z	OMF985001022001503	5410439130998	25	35.03	22	15	32
24	MF985,24150 Z	OMF985001024001503	5410439131018	25	39.55	24	15	36
24	MF985,24200 Z	OMF985001024002003	5410439131025	25	39.55	24	15	36
30	MF985,30200 Z	OMF985001030002003	5410439131049	10	50.85	30	19	46



material : Steel class 10	materiaal : Staal klasse 10	matière : Acier classe 10	Werkstoff : Stahl Klasse 10
type : metric fine thread	type : metrisch fijn	type : filet métrique fin	Typ : metrisch Feingewinde
surface : zinc plated Cr3+	oppervlak : verzinkt Cr3+	surface : zingué Cr3+	Oberfläche : verzinkt Cr3+

Technical properties | Technische gegevens | Données techniques | Technische Daten

M	OLD CODE	NEW CODE	EAN	BOX	e min.	h max.	m min.	s max.
8	MF985,08100 Z-	OMF985101008001003	5410439003988	100	14.38	8	5.5	13
10	MF985,10100 Z-	OMF985101010001003	5410439003995	100	18.9	10	6.5	17
10	MF985,10125 Z-	OMF985101010001253	5410439004008	100	18.9	10	6.5	17
12	MF985,12100 Z-	OMF985101012001003	5410439091657	100	21.1	12	8	19
12	MF985,12125 Z-	OMF985101012001253	5410439269537	100	21.1	12	8	19
12	MF985,12150 Z-	OMF985101012001503	5410439091664	100	21.1	12	8	19
14	MF985,14150 Z-	OMF985101014001503	5410439091671	50	24.49	14	9.5	22
16	MF985,16150 Z-	OMF985101016001503	5410439091688	50	26.75	16	10	24
18	MF985,18150 Z-	OMF985101018001503	5410439091695	50	29.56	18.5	13	27
20	MF985,20150 Z-	OMF985101020001503	5410439091718	50	32.95	20	14	30
20	MF985,20200 Z-	OMF985101020002003	5410439091725	50	32.95	20	14	30
22	MF985,22150 Z-	OMF985101022001503	5410439091732	25	35.03	22	15	32
24	MF985,24150 Z-	OMF985101024001503	5410439091756	25	39.55	24	15	36
24	MF985,24200 Z-	OMF985101024002003	5410439091763	25	39.55	24	15	36
30	MF985,30200 Z-	OMF985101030002003	5410439091800	10	50.85	30	19	46