



Den Braven

Technical Data Sheet

Zwaluw® Joint Fix®

High quality hardening joint repair filler in brickwork



Product Description

Zwaluw Joint Fix® is a high quality hardening joint repair filler based on a polymer dispersion and additives for both in and outdoor joint applications.

avantages

- Ready to use repair mortar. Paintable with waterbased and synthetic paints. Perfect adhesion with the use of a primer, even on damp substrates. Interior and exterior usage. Nearly non smelling. Easy to apply and clean. Non corrosive towards metals.

Applications

Zwaluw Joint Fix® has been developed especially for durable jointing and repairing of new and damaged joints between stone strips and Façade masonry. Zwaluw Joint Fix® is weather and rain resistant some hours after application. Also for sealing connection joints between lead and brickwork.

spécifications techniques

Température d'application		+5°C till +40°C
base		Acrylaat dispersion
Densité		1,74 g/ml
Flow	ISO 7390	< 2 mm
Résistance gel lors du transport		Till -15°C
Shore-A hardness		80
Shrinkage		5%

limites

- Not suitable for continuous submersion in water.
- Not suitable for PE, PP, PC, PMMA, PTFE, neoprene and bituminous substrates.
- *Exterior applications only in good dry weather conditions for at least 5 hours after application.
- Not suitable to absorb movement

Préparations et de finition

Application temperature +5°C till +40°C (applies to environment and substrate). All surfaces must be solid and clean, dry and free from dust and grease. Substrate to be cleaned from all loose particles, porous substrate does not require to be absolutely dry. Very porous substrates like: Gypsum, airated concrete, limstone, etc, need to be primed with a mixture of 1 part zwaluw Joint Fix® and 2 parts water. Adhesion tests prior to application are recommended. Press 5 minutes after application zwaluw Joint Fix® into the joint and finsih with a joint spatula. Do not apply when exposed to extreme sunlight. Remove excessive material after 5 - 10 minutes with a dustpan or wet sponge from the joints and brickwork. During curing the product becomes darker. Tools and hands to be cleaned with water. Apply with the V-nozzle supplied with the cartridge.

Aptitude à la peinture

Zwaluw Joint Fix® is paintable after full drying of sealant. During curing product will show shrinkage, which can cause cracking of the paint. Excellent paintable with water based and synthetic Paints. Painting with high filled water based paints can create cracking. Recommend to test compatability with paint prior to application.

Nettoyage

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

Couleur (s)

- Grey

Conditionnement

- Cartridge 310 ml

Durée de conservation



Den Braven

Better
results
through
knowledge

Technical Data Sheet

Zwaluw® Joint Fix®

High quality hardening joint repair filler in brickwork

Shelflife of 12 months after production date. Stored in a dry place in unopened original packaging between +5°C and +25°C.

Santé et sécurité

Product Health and Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.