


Fers - T



Désignation Benaming	Dimensions Afmetingen						Poids commercial Handels-gewicht
	h	b	s/t	r	r ₁	r ₂	
	mm						
T + h = mm							kg/m
T20	20	20	3	3	1,5	1	0,90
T25	25	25	4	4	2,0	1	1,31
T30	30	30	4	4	2,0	1	1,80
T35	35	35	5	5	2,5	1	2,38
T40	40	40	5	5	2,5	1	3,02
T45	45	45	6	6	3,0	1,5	3,74
T50	50	50	6	6	3,0	1,5	4,53
T60	60	60	7	7	3,5	2	6,35
T70	70	70	8	8	4,0	2	8,48
T80	80	80	9	9	4,5	2	10,88
T100	100	100	11	11	5,5	3	16,72
T120	120	120	13	13	6,5	3	23,68
T140	140	140	15	15	7,5	4	31,92

Mètres par t Meters per t	Section Sectie	Surface Oppervlakte		Désignation Benaming
		A _L	A _G	
		m ² /m	m ² /t	
L _G	A			T + h = mm
m/t	cm ²	m ² /m	m ² /t	
1116	1,12	0,075	83,71	T20
762	1,64	0,094	71,65	T25
556	2,25	0,114	63,33	T30
421	2,97	0,133	55,98	T35
332	3,77	0,153	50,73	T40
268	4,67	0,171	45,77	T45
221	5,66	0,191	42,18	T50
157	7,94	0,229	36,05	T60
118	10,60	0,268	31,60	T70
92	13,60	0,307	28,22	T80
60	20,90	0,383	22,91	T100
42	29,60	0,459	19,38	T120
31	39,90	0,537	16,82	T140